STYLISH REMOTE CONTROLLER



Perfecting the Air





2 COLOURS

Available in two attractive colours, the remote controller adds style and sophistication to any indoor space. Measuring just 85×85 mm, the remote controller is extremely compact and will become a fluid part of any background.



White
RAL 9003 (Glossy)
BRC1H63W



Black
RAL 9005 (Matt)
BRC1H63K



USER FRIENDLY INTERFACE

The remote controller combines functionality and simplicity. The minimalistic touch button control enlarges the display and makes the remote controller both easy and enjoyable to use.



Fan Speed



Operation mode (Cooling, Heating, Auto, etc.)



Airflow Direction





Easy and direct access to main functions








reddot design award





SLEEK STYLISH DESIGN

Much like the perfection of its circular shape, the remote controller gives you perfect control over your individual climate.









ZIGBEE

Now compatible with Zigbee sensors for your convenience and comfort.

- Discover our range of sensors, including CO₂ sensors, temperature/humidity sensors, motion sensors, and door/ window sensors.
- Sensors seamlessly interlock with the Stylish Controller via wireless Zigbee 3.0 communication (max 10m line of sight), delivering enhanced functionality.



DAIKIN APP FOR INSTALLER

Simplifies the advanced settings such as field settings and set point range.

- Visual interface simplifies advanced settings such as energy saving activation, setting restrictions, etc.
- Easy and quick commissioning, saves time and cost for installers.
- Featuring Bluetooth low energy technology.



DAIKIN

-0+

EO3



FUNCTIONS LIST

	Function	Remote controller			Application (Smartphone)		Remarks
		Basic operation	Administrator Menu	Installer menu	Owner / Administator mode	Installer mode	
Basic Function	Operation Start / Stop	√					
	Operation mode	√					
	Airflow rate (Fan speed)	√					The number of airflow steps depends on indoor unit model.
	Airflow direction Setpoint	√ √					
	Ventilation rate	V /					
	Ventilation mode	· /					Available for only when Heat Reclaim Ventilator is connected.
	Celsius / Fahrenheit	✓			✓	✓	
	Ventilation related icons	✓					Display the icons of Fresh up, Nighttime free cooling operation, etc. when it is set.
	OFF timer NEW	✓					Period can be preset from 1 to 96 hours in 1-hour increments.
	Weekly schedule timer				✓	√	Up to 5 operations can be set for each day of the week. 3 independent schedules can be set. (e.g. summer, winter, mid-season) The operation that can be set is ON/OFF, and the set temperature for cooling/heating is set. The temperature set at OFF is used as the setback temperature.
	Setpoint range set				√	✓	
Energy	Sensing sensor low mode Sensing sensor stop mode				√ ✓	√ √	Applicable for the indoor unit with infrared sensors.
Saving	Sensor results display			√	V	√	Sensor results from Heat Reclaim Ventilator, thermistor, and Zigbee™ sensors can be displayed up to 3 items on the Information
	Sensor connection (NEW)				✓	√	screen. - Temperature: Display, Air conditioner operation ON/OFF - CO2: Display, Change ventilation rate - Door/Window: Air conditioner operation ON/OFF - Motion: Air conditioner operation ON/OFF - Humidity: Display only
						✓	Register / delete Zigbee™ sensor to remote controller.
	Airflow direction range (for Floor standing type)					✓	
	Individual airflow direction control				√	√	Applicable for the indoor unit with this function.
Comfort	Setback Draft prevention				√ √	√ √	Applicable for the indoor unit with this function.
	Auto cooling / heating changeover				· · · · · · · · · · · · · · · · · · ·	√	This function shall not be used when Wireless LAN connecting adaptor for SkyAir is used.
	(for Heat pump type)				v	√	adaptor for SkyAir is used. Allowed to disable the settings.
	Setpoint minimum differential Streamer function (Mold proof operation)			√	٧	٧	Streamer ON/OFF setting by field setting with remote controller. Streamer operation ON and streamer function error icons are
	Filter sign (Reset)	✓					displayed. ' Filter sign notifies the time to clean the filter of indoor unit.
Filter Indicator	Element sign (Reset)	√					Element sign notifies the time to clean the element of air purifier unit when the indoor unit connected with air purifier unit.
muicator	•	· ·			√	,	
Option	Prohibit function (user menu items) Prohibit function (Center button prohibit)				√	√ √	Set whether user can change basic functions in each menu.
	Prohibit function (Operation Mode)				√	√	Limit available operation mode from remote controller in each mode.
Display	Contrast adjustment		√ ·				
	LCD backlight adjustment	/	✓		√ 	√	
	LED brightness adjustment (screen Backlight ON)	√ /			√	√ /	The brightness of LED (Status indicator) when backlight is On or Off can be changed respectively. Also, LED can be turned off.
	LED brightness adjustment (screen Backlight OFF)	✓			✓	✓	can be changed respectively. Also, LED call be turned on.
	Auto display OFF			√	,	√	
Remote Controller Setting	Date and time setting Daylight Saving Time (DST)		✓		√ √	√ √	
	Remote Controller field settings			√	· ·	√	
	Display icon customization			√		√	
	Remote controller thermostat temperature offset BLE settings (Pairing screen)		√	√ ·	√	√ √	
	Set / release Cooling / Heating master (for VRV)			✓			Decision procedure for the Master Control is same as BRC1E63.
	Administrator Password Settings		✓		✓	✓	Default is no password
0.71	Installer Password Settings			✓		√	· ·
OTA	OTA (Over The Air) NEW					✓	Update the remote controller software through the BLE app.
Hotel	Hotel display (NEW)	✓			✓	✓	A simple display for hotel guests. Operation mode and set temperature can be changed by simply pressing three buttons on the Home screen without using the menu button.

SPECIFICATIONS

MODEL				BRC1H63W	BRC1H63K	
Colour				White	Black	
Dimensions Height x Width x Depth		mm	85 x 8	5 x 25		
Weight			g	110		
LCD backlight				Available		
Status indicator (LED) Red Green				Normal operation		
				Error alert		
				Bluetooth connection		
Maximum number of connectable indoor units				1 group (up to 16 indoor units)		
Wiring connections	For connection with indoor			P1-P2 wired connection from indoor unit		
Wiring connections	Size	Size mm ²		0.75 ~ 1.25		
Bluetooth® wireless technology	oth® wireless technology Protocol			Bluetooth® low energy 4.2 or higher		
Zigbee [™] Protocol				Zigbee™ 3.0		
Application				DAIKIN APP for installer		
Application operation system				Apple iOS 16 or higher, Android 13 or higher		

